

TC3700 Tire Changer

Easy-to-use center-clamp tire changer



Key features at a glance



OPTIONAL

Bead Press Arm

- ✓ Assists mounting difficult assemblies



Blast Inflation

- ✓ Directs bursts of compressed air to easily seat the bead



Adjustable column

- ✓ 12" to 28" range

Motor and drive

- ✓ 15- and 7-rpm clockwise speeds, 15 rpm counterclockwise speed
- ✓ 850 ft-lbs. of torque

OPTIONAL

PowerOut™ Bead Loosener

- ✓ Ergonomic control handle makes large assembly service easy
- ✓ Familiar side shovel design with standard protector sleeve



TC3715SS shown



Mount/Demount Head

- ✓ Polymer mount/demount head resists marring rims
- ✓ Vertical locking head protects wheel face



PATENTED

Intuitive Center-Clamp System

- ✓ Simple clamping technique
- ✓ Cam action multiplies clamping force
- ✓ Three height positions



NEW

Split Bead Roller System

- ✓ New controls simplifies use
- ✓ Match-mounting made easy
- ✓ Easy bottom bead demounting with roller



Match-Mounting & Bead Massage Made Easy

Hunter's center-clamp tire changers and Road Force® wheel balancers:

- ✓ Eliminate vibration problems
- ✓ Reduce comebacks
- ✓ Increase customer satisfaction

The bead rollers safely hold the tire stationary while the rim is rotated to complete match-mounting.



Models



TC3715SS TC3715 TC3700SS TC3700

Bead press arm	✓	✓		
PowerOut™ Bead Loosener	✓		✓	

Add "W" to the end of any model number to include wheel lift

Specifications

Clamping system rotating speed	7 & 15 CW 15 CCW
Torque	850 ft.-lbs.
Electrical requirements	220V, 1 ph, 15A
Air pressure operating range	115-175 psi
Tire diameter	50 in.
Hydraulic bead-loosening system	
Max. bead roller opening width	21 in.
Diameter range	12-28 in.
Bead roller power; each roller	4,170 lbs. @ 140 psi
Side shovel (optional)	
Max. bead-loosening opening width	17 in.
Shovel power	6,600 lbs. @ 140 psi
Max. space dimensions	
Width	43 in.
Height	72 in.
Depth	43 in.
Machine weight	560 lbs.

* Some dimensions, capacities and specifications may vary depending on tire and wheel configurations.

Be sure to check out other literature for more quality products from Hunter Engineering.



Optional accessories



Flange plate for chrome-clad and reverse wheels *RP6-G1000A87*
Useful for chrome-clad wheels and/or reverse wheels where maximum finish protection is needed.



Flange plate for chrome-clad wheels *RP6-G1000A123*
Simplified flange plate for chrome-clad wheels only.



19.5" adaptor *20-2341-1*
Adapts large centerbore wheels to center-clamp tire changers.



Wheel lift package *20-2944-1*
Optional wheel lift eases servicing of large assemblies. Allows for more careful handling of expensive wheels.

HUNTER
Engineering Company
www.hunter.com