



TIRE CHANGER



760

SPECIFICATIONS

Outer-Clamping Range:	12"-24"
Inner-Clamping Range:	14"-26"
Maximum Tire Diameter:	44"
Maximum Tire Width:	19"
Air Supply Requirements:	120-145 PSI
Power Requirements:	110V, 1PH, 60HZ
Table Motor:	1.5HP
Built-in Bead Blaster:	YES
Warranty:	1 YEAR
Pneumatic Helper:	Optional
Shipping Weight:	850LBS.



THE OPTIONAL JTC HELPER COMES WITH THREE STANDARD FEATURES: BEAD DISC LIFTER, BEAD ROLLER, AND A BEAD PRESS THAT ARTICULATES AS YOU DE-MOUNT OR MOUNT A TIRE. THIS IS ALL CONTROLLED BY A PNEUMATIC VALVE WITH A TOGGLE SWITCH.



OPTIONAL ACCESSORIES



BEAD PUSHER




NYLON HEAD V.2



JAW COVERS



BEAD CLAMP



MC/ATV ADAPTERS(4)



NYLON INSERT

Distributed By:



JERICO EQUIPMENT & SUPPLY
#208 1730 COAST MERIDIAN RD.,
PORT COQUITLAM, B.C.
CANADA V3C 3T8
SALES (604) 762-5050
SERVICE (604) 808-5100
PARTS (604) 506-7631

We reserve the right to make changes in specifications without notice and without making changes retroactive.